

UNIVERSAL 100

Opportunity + Partnership = Success

Reiber Style Gasketed Pipe

Nominal Pipe Size Inches	Foot per Std Pkg	Specs	100 PSI SDR 41	125 PSI SDR 32.5	160 PSI SDR 26	200 PSI SDR 21	200 PSI/SDR 21 PRP/Reclaim
2 1/2"	2480	Lbs Per Ft				0.768	0.768
3"	1760	Lbs Per Ft				1.000	1.000
4"	960	Lbs Per Ft				1.858	1.858
6"	400	Bell Dia. Inches	8.34	8.34	8.34	8.34	8.34
		Lbs Per Ft	2.126	2.652	3.299	4.036	4.036
8"	280	Bell Dia. Inches	10.56	10.56	10.56	10.56	10.56
		Lbs Per Ft	3.589	4.491	5.578	6.825	6.825
10"	80	Bell Dia. Inches	13.27	13.27	13.27	13.27	13.27
		Lbs Per Ft	5.577	6.992	8.652	10.599	10.599
12"	60	Bell Dia. Inches	15.50	15.50	15.50	15.50	15.50
		Lbs Per Ft	7.851	9.829	12.183	14.913	14.913

Gasketed pressure pipe conforms to ASTM D2241 for standard dimension ratios. PVC gasketed pipe is standard white. Rubber rings conform to F477 specifications. Designed for installed cost savings. Most sizes can be handled manually, so there is no need for costly installation equipment. Use the backhoe for excavating and backfilling only. Dig more trench, lay pipe faster, save more in costs per foot installed.

NOTE: Pipe to be joined by block and tackle or warranty is void.